
Ambermat 150W/m² Heating Mat

12

The Amber underfloor heating mats offer the perfect solution to a warmer home. Simple to use and quick to install, the AmberMat can be easily rolled out and is designed to fit under a range of floor coverings.

The AmberMat is a strong self-adhesive mat, with 360° fully screened twin conductor encompassed within a tough yellow PVC outer sheath (non UV stable). With just a 4mm thickness it can be easily and quickly fitted directly onto the existing floor, making it perfect for renovations.





Benefits

- Simple Installation
- Minimal Installation Height
- 100% Earth Shield
- 4 Metre Cold Tail

Technical Data		
Operation voltage	220 - 240V~	
Power Output	150 W/m² @230V~	
Construction	Round, twin conductor	
	with 360° screening,	
	one cold tail	
Maximum ambient temp	65°C	
Cable thickness	4mm	
Deformation strength	600N	
Pulling strength	120N	
Conductor insulation	FEP	
Outer sheath	PVC	
Screen	100% coverage, alu-foil,	
	0.5mm² tinned copper	
	drain wire	
Cold lead	4m DTWB, 2 x 1.0mm ² ,	
	earthed	
Min installation temp	-5°C	
Bending radius	6xØ	
IP Class	IPX7	

Product Code	Mat Coverage (m²)	Resistance (Ohms)	Output (W)
A150005	0.5	705	75
A150010	1	353	150
A150015	1.5	235	225
A150020	2	176	300
A150025	2.5	141	375
A150030	3	118	450
A150035	3.5	101	525
A150040	4	88.2	600
A150050	5	70.5	750
A150060	6	58.8	900
A150070	7	50.4	1050
A150080	8	44.1	1200
A150090	9	39.2	1350
A150100	10	35.3	1500
A150120	12	29.4	1800

